

STOCK POT COMMERCIAL INDUCTION COOKTOP

SPCI151PH



Key Features

- ✓ High-efficiency induction technology for fast and precise cooking.
- \checkmark 5,000W power output for heavy-duty cooking applications.
- ✓ Designed for stock pots, ideal for boiling, simmering, and slow cooking.
- √ Compact and space-saving design, perfect for professional kitchens.
- ✓ Durable construction for long-term reliability.
- ✓ Energy-efficient operation, reducing overall power consumption.
- ✓ User-friendly controls for precise temperature adjustments.
- √ Safety features including overheating protection and automatic pan detection.

Advantages Over Traditional Stovetops

- \checkmark Fast heating and instant response to temperature adjustments.
- ✓ Lower heat loss compared to gas and electric stoves.
- √ Safety no open flames.
- ✓ Easy maintenance smooth glass-ceramic surface.

The EURODIB **SPCII51PH** is a high-performance commercial stock pot induction cooktop, designed for professional kitchens that require efficiency, precision, and durability.

Operating at 240V, 60Hz, this unit delivers powerful and consistent heating with 5,000W of induction power, ensuring rapid heat-up times and precise temperature control. Its compact and durable design makes it an excellent choice for high-demand professional kitchens that require heavy-duty cooking capabilities.

The **SPCII51PH** is built with durable materials and advanced safety features, making it a reliable and energy-efficient solution for busy commercial kitchens.

Technical Specifications

Model	SPCI151PH
Power Supply	1 phase
Voltage	240V
Frequency	60Hz
Power Output	5,000W
Auto Shutoff Timer	6 hours
Dimensions (L × W × H)	25" x 22" x 20"
Shipping Dimensions (L × W × H)	22.6" x 25.3" x 25.6"
Weight	62.86 lbs
Shipping Weight	68.34 lbs
Glass Type	Schott Glass – Made in Germany
Maximum Allowable Load for Cooktop	176 lbs
Suitable for Induction Pots & Pans	Base Diameter: ø140 - 410 mm (5.5" - 16.1")
Glass Size	15.75" × 15.75"
Warranty	1 year parts & labor except for glass surfaces

















